

W0029 Pebbles

Collection	Stonen Collection
Product Type	Tile
Style Number	W0029
Construction	Intrepid - Multi-Level Cut/Loop
Fiber	Lextron Enviro-Green Nylon
Dye Method	100 % Solution Dyed
Primary Backing	Woven PET
Secondary Backing	Ethos with Omnicoat

Specifications

Size	18"x 36" (12 tiles per Box / 6.0 sq yards per box)
Gauge	1/10
Stitches per Inch	9
Tufted Weight	26 oz per sq/yd
Total Weight	115.26 oz
Density	10,334
Finished Pile Thickness	.085 inches
Pattern Repeat	Tile
Overall Thickness	.295 inches


Performance

Traffic Class (TARR)	Heavy
Pill Test	Pass
Radiant Panel	Class I
Flammability	ASTM E 648 Class I
Smoke Density	ASTM E 662 Less than 450
LEED Info	Green Label Plus Certified – GLP8320

Warranty **10 Year Limited Warranty**

Available Customs

Backings	N / A
Tiles Sizes	24"x 24" (15 tiles per Box / 6.667 sq yards per box) 9"x 36" (24 tiles per Box / 6 sq yards per box)

Enviro-Green yarn has 10% pre-consumer recycled content. 
 Recommended for heavy (public space) carpet traffic levels.

NOTE: Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104.
 Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction.
IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.