

## **W0019 Sandstone**

Collection	<b>Stonen Collection</b>
Product Type	<b>Tile</b>
Style Number	<b>W0019</b>
Construction	<b>Intrepid - Multi-Level Cut/Loop</b>
Fiber	<b>Lextron Enviro-Green Nylon</b>
Dye Method	<b>100 % Solution Dyed</b>
Primary Backing	<b>Woven PET</b>
Secondary Backing	<b>Ethos with Omniccoat</b>

### **Specifications**

Size	<b>18"x 36" (12 tiles per Box / 6.0 sq yards per box)</b>
Gauge	<b>1/10</b>
Stitches per Inch	<b>9</b>
Tufted Weight	<b>26 oz per sq/yd</b>
Total Weight	<b>115.26 oz</b>
Density	<b>10,334</b>
Finished Pile Thickness	<b>.085 inches</b>
Pattern Repeat	<b>Tile</b>
Overall Thickness	<b>.295 inches</b>


### **Performance**

Traffic Class (TARR)	<b>Heavy</b>
Pill Test	<b>Pass</b>
Radiant Panel	<b>Class I</b>
Flammability	<b>ASTM E 648 Class I</b>
Smoke Density	<b>ASTM E 662 Less than 450</b>
LEED Info	<b>Green Label Plus Certified – GLP8320</b>

**Warranty** **10 Year Limited Warranty**

### **Available Customs**

Backings	<b>N / A</b>
Tiles Sizes	<b>24"x 24" (15 tiles per Box / 6.667 sq yards per box)</b> <b>9"x 36" (24 tiles per Box / 6 sq yards per box)</b>

Enviro-Green yarn has 10% pre-consumer recycled content.   
Recommended for heavy (public space) carpet traffic levels.

**NOTE:** Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104.  
Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction.

**IT IS NOT A CARPET DEFECT**, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.